

# Declaration of Performance for the construction product

## StoLevell Duo plus



**Unique identification code of the product-type** PROD0977 StoLevell Duo plus  
 general purpose plastering mortar (GP) CS III  
*See the container imprint for the batch number.*

**Intended use/es** Onto walls, ceilings, pillars, and separating walls in exteriors and interiors

**Manufacturer** Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

**System/s of AVCP** system 4 (Reaction to fire)  
 system 4 (applies to all other "Essential characteristics" in the table)

**Harmonised standard** EN 998-1:2016

**Notified body/ies** Not relevant

**European Assessment Document** Not relevant

**European Technical Assessment** Not relevant

**Technical Assessment Body** Not relevant

**Appropriate Technical Documentation and/or Specific Technical Documentation** Not relevant

### Declared performance/s

Essential characteristics	Performance	AVCP system	Harmonised technical specification
Reaction to fire	A2-s1, d0	system 4	EN 998-1:2016
Water absorption	$W_c$ 2		EN 998-1:2016
Bond strength on concrete	$\geq 0,25$ N/mm <sup>2</sup> / fracture pattern B		EN 998-1:2016
Durability	NPD		EN 998-1:2016
Dangerous substances	NPD		EN 998-1:2016
Water vapour diffusion-equivalent air layer thickness $\mu$	$\leq 25$		EN 998-1:2016
Thermal conductivity	$\leq 0,45$ W/(m*K) für P=50%		EN 998-1:2016
Thermal conductivity	$\leq 0,49$ W/(m*K) für P=90%		EN 998-1:2016

*NPD = no performance determined*

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Attachment: Safety Data Sheet

The current valid version of the declaration of performance is available at [www.sto.com/ce](http://www.sto.com/ce).

CE	<p><b>Sto SE &amp; Co. KGaA</b> Ehrenbachstraße 1 D-79780 Stühlingen</p>
01-0087-3	07
<p><b>PROD0977 StoLevel Duo plus</b> <b>EN 998-1:2016 general purpose plastering mortar (GP) CS III</b> Onto walls, ceilings, pillars, and separating walls in exteriors and interiors</p>	
Reaction to fire	A2-s1, d0
Water absorption	$W_c$ 2
Water vapour diffusion-equivalent air layer thickness $\mu$	$\leq 25$
Thermal conductivity	$\leq 0,45 \text{ W}/(\text{m}\cdot\text{K})$ für P=50%Table value $\leq 0,49 \text{ W}/(\text{m}\cdot\text{K})$ für P=90%Table value
Bond strength on concrete	$\geq 0,25 \text{ N}/\text{mm}^2$ / fracture pattern B
Durability	NPD
Dangerous substances	NPD