

Declaration of Performance for the construction product

StoSilco[®] K



Unique identification code of the product-type PROD0903 StoSilco[®] K
render/plaster with organic binding agents
See the container imprint for the batch number.

Intended use/es onto walls, ceilings and pillars in exteriors

Manufacturer Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

System/s of AVCP System 3 (reaction to fire)
system 4 (applies to all other "Essential characteristics" in the table)

Harmonised standard EN 15824:2017

Notified body/ies MFPA Leipzig GmbH NB 0800

European Assessment Document Not relevant

European Technical Assessment Not relevant

Technical Assessment Body Not relevant

Appropriate Technical Documentation and/or Specific Technical Documentation Not relevant

Declared performance/s

| Essential characteristics | Performance | AVCP system | Harmonised technical specification |
|---------------------------|-------------|-------------|------------------------------------|
| Reaction to fire | A2-s1, d0 | System 3 | EN 15824:2017 |
| Water absorption | W 3 | | EN 15824:2017 |
| Water vapour permeability | V 1 | | EN 15824:2017 |
| Thermal conductivity | NPD | | EN 15824:2017 |
| Durability | NPD | | EN 15824:2017 |
| Dangerous substances | NPD | | EN 15824:2017 |
| Bond strength | ≥ 0,3 MPa | | EN 15824:2017 |

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



30.04.2019
Sto SE & Co. KGaA D-79780 Stühlingen

Francisco Ramos / Head of Business Fields Facade and Interiors

Attachment: Safety Data Sheet

The current valid version of the declaration of performance is available at www.sto.com/ce.



Sto SE & Co. KGaA

Ehrenbachstraße 1

D-79780 Stühlingen

01-0064-2

10

NB 0800

PROD0903 StoSilco® K
EN 15824:2017 render/plaster with organic binding agents

onto walls, ceilings and pillars in exteriors

| | |
|---------------------------|-----------|
| Reaction to fire | A2-s1, d0 |
| Water absorption | W 3 |
| Thermal conductivity | NPD |
| Bond strength | ≥ 0,3 MPa |
| Durability | NPD |
| Water vapour permeability | V 1 |
| Dangerous substances | NPD |