

# Declaration of Performance for the construction product

## Stolit® K



**Unique identification code of the product-type** PROD0714 Stolit® K  
render/plaster with organic binding agents  
*See the container imprint for the batch number.*

**Intended use/es** onto walls, ceilings and pillars in exteriors

**Manufacturer** Sto SE & Co. KGaA, Ehrenbachstr. 1, D-79780 Stühlingen

**System/s of AVCP** System 3 (reaction to fire)  
System 4 (applies to all other "Essential characteristics" in the table)

**Harmonised standard** EN 15824:2017

**Notified body/ies** MPA Stuttgart NB 0672

**European Assessment Document** Not relevant

**European Technical Assessment** Not relevant

**Technical Assessment Body** Not relevant

**Appropriate Technical Documentation and/or Specific Technical Documentation** Not relevant

### Declared performance/s

Essential characteristics	Performance	AVCP system	Harmonised technical specification
Reaction to fire	A2-s1, d0	System 3	EN 15824:2017
Water absorption	W 3		EN 15824:2017
Water vapour permeability	V 2		EN 15824:2017
Thermal conductivity	NPD		EN 15824:2017
Durability	NPD		EN 15824:2017
Dangerous substances	NPD		EN 15824:2017
Bond strength	≥ 0,3 MPa		EN 15824:2017

*NPD = no performance determined*

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



09.12.2019  
Sto SE & Co. KGaA D-79780 Stühlingen

Francisco Ramos / Head of Business Fields Facade and Interiors

Attachment: Safety Data Sheet

The current valid version of the declaration of performance is available at [www.sto.com/ce](http://www.sto.com/ce).



Sto SE & Co. KGaA  
Ehrenbachstraße 1  
D-79780 Stühlingen

01-0031-3

10

NB 0672

**PROD0714 Stolit® K**  
**EN 15824:2017 render/plaster with organic binding agents**  
onto walls, ceilings and pillars in exteriors

Reaction to fire	A2-s1, d0
Water absorption	W 3
Thermal conductivity	NPD
Bond strength	≥ 0,3 MPa
Durability	NPD
Water vapour permeability	V 2
Dangerous substances	NPD